













Thermocouple Extension Wire (Types K & T)

Overview

- Thermocouple extension wire for Types K & T
- Unshielded PVC ,Fiberglass Jackets,SUS Braided & Teflon jacket.
- Others insulation ,jacket material ,size and specification for thermocouple extension wire can be upon request.

| Thermocouple Extension Wire | | | | | | |
|---|------|----------------|-----------------------------------|----------------------------|------------------------------|-------------------------|
| Part Number | Type | Conductors | Conductor Insulation | Jacket Material | Continuos Temperature Rating | Specification Size (mm) |
| A1F0.6KXH-GAB | K | 2,Solid | Red (+) Black (-) | SUS Braided/ Fiberglass | 0 to 200°C | 0.6mm x 2 |
|  | | | | | | |
| A1KX1/0.6(22AWG) FG-SUS | K | 2,Solid | Red tracer (+) Blue tracer (-) | SUS Braided/ Fiberglass | 0 to 200°C | 0.6mm x 2 |
|  | | | | | | |
| A1KX-7/0.2-H-(SOS)-H | K | 2,Stranded (S) | Red (+) Blue tracer (-) | SUS Braided/ Fiberglass | 0 to 200°C | 0.2mm x 7S |
|  | | | | | | |
| A1F4/0.3X2KXH-GAB (BLUE) | K | 2,Stranded (S) | Red (+) Black (-) | SUS Braided/ Fiberglass | 0~200°C | 0.3mm x 4S |
|  | | | | | | |
| A1KX1/0.64(22AWG) FG-SUS IEC (ROUND) | K | 2,Solid | Green (+) White (-) | SUS Braided/ Fiberglass | 0 to 200°C | 0.64mm x 2 |
|  | | | | | | |

Thermocouple Extension Wire (Types K & T)

| Thermocouple Extension Wire | | | | | | |
|--|------|----------------|-----------------------------|----------------------------|------------------------------|-------------------------|
| Part Number | Type | Conductors | Conductor Insulation | Jacket Material | Continuos Temperature Rating | Specification Size (mm) |
| A1KCC-H4/0.6X2 | K | 2,Stranded (S) | Red tracer (+) White (-) | Fiberglass (Blue) | 0 to 200°C | 0.6mm x 4S |
|  | | | | | | |
| A1KCC-H7/0.3X2 | K | 2,Stranded (S) | Red tracer (+) White (-) | Fiberglass (Blue) | 0 to 200°C | 0.3mm x 7S |
|  | | | | | | |
| A1KX-H0.5X2 | K | 2,Solid | Yellow (+) Red (-) | Fiberglass (Brown +Yellow) | 0 to 400°C | 0.5mm x 2 |
|  | | | | | | |
| A1KCCG7/0.3X2 | K | 2,Stranded (S) | Red (+) White(-) | PVC (Blue) | 0 to 200°C | 0.3mm x 2 |
|  | | | | | | |
| A1KX-F0.6X2JIS | K | 2,Solid | Red (+) White(-) | Teflon (Blue) | 0 to 200°C | 0.6mm x 2 |
|  | | | | | | |
| A1KX-F-ANSI-TG0.5X2 | K | 2,Solid | Red (+) Yellow (-) | Teflon (Brown) | 0 to 200°C | 0.5mm x 2 |
|  | | | | | | |
| A1TT-T-24ANSI | T | 2,Solid | Red (+) Blue (-) | Teflon (Brown) | 0 to 200°C | 0.5mm x 2 |
|  | | | | | | |